

Carlsbro Holdings Ltd

Unit 11, Torc MK, Chippenham Drive, Milton Keynes, MK10 0BZ.United Kingdom Tel-+44(0)1908 281072 Web: www.carlsbro.com Email: sales@carlsbro.com



IMPORTANT SAFETY SYMBOLS





The symbol is used to indicate that some hazardous live terminals are involved within this apparatus, even under the normal operating conditions, which may be sufficient to constitute the risk of electric shock or death.



The symbol is used in the service documentation to indicate that specific component shall be replaced only by the component specified in that documentation for safety the component specified in that documentation for safety reasons.

- Protective grounding terminal
- ~ Alternating current/voltage
- Hazardous live terminal

ON: Denotes the apparatus is turned on.

OFF: Denotes the apparatus is turned off.

WARNING: Describes precautions that should be observed to prevent the danger of injury or death to the operator.

CAUTION: Describes precautions that should be observed to prevent danger of the apparatus.



Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.

IMPORTANT SAFETY INSTRUCTIONS


other appliances that produce heat.

☐Read these instructions.	☐Keep these instructions.
☐Heed all warning.	□Follow all instructions.
□Water & Moisture The apparatus should be protected from moisture and rain, can not used near water, for example: near bathtub, kitchen sink or a swimming pool, etc.	
□Heat	
The apparatus should be located away from the heat source such as radiators, stoves or	



50 SC/50 DC valve amplifier

PANEL







PREAMP SECTION

All-valve 50w single or twin channel amp head. The new twin channel amp head has switchable channels & two master volumes which are footswitchable. The valve compliment of 4x 12AX7's (2x on SC) and 2x El34's gives you 50w of incredible power @ 8 or 16 Ω 's. The preamp has a host of feature benefits including, hi and low sensitivity jack inputs,3 band EQ using silvered mica capacitors, sleep mode automatic muting with no input present, mains on/off & standby switches are standard and you have 115V/230V option operation. Jack outputs are 2 @ 8 Ω and 1 @ 16 Ω allowing choice of cabinets. Tough ply construction, durable covering & metal corners essential for on the road use.

EVO50 DC footswitch function: The footswitch can connect with two channels.

Footswitch 1: Switching master1 and master2

Press select key on the panel, it switches channel and channel 2

Footswitch 2: It turns on/off FX loop external effector.

Press boost key on the panel, it turns on/off boost function